



ISOMETRIC VIEW

NOTES:

1. ALL AGGREGATE SUB-BASE SHALL BE MECHANICALLY COMPACTED.
2. SIDEWALK THICKNESS AT CURB RAMPS SHALL BE A MINIMUM OF 6" PCC ON 2" AGGREGATE SUB BASE.
3. SIDEWALK CONSTRUCTION SHALL FOLLOW APPLICABLE IDOT STANDARDS.
4. SIDEWALKS SHALL FOLLOW CURRENT ADA GUIDELINES.
5. PROVIDE AT LEAST ONE (1) TOOLED OR SAWCUT CONTROL JOINT IN THE CURB. JOINT SHALL BE INLINE WITH SIDEWALK EDGE.
6. DETECTABLE WARNING TILE COLOR SHALL BE "BRICK RED" OR AS APPROVED BY THE CITY OF BATAVIA.

APPLICABLE IDOT STANDARD DETAILS OR LATEST REVISION THEREOF:

| | |
|-----------|--|
| 424001-07 | PERPENDICULAR CURB RAMPS FOR SIDEWALKS |
| 424006-01 | DIAGONAL CURB RAMPS FOR SIDEWALKS |
| 424011-01 | CORNER PARALLEL CURB RAMPS FOR SIDEWALKS |
| 424016-01 | MID-BLOCK CURB RAMPS FOR SIDEWALKS |
| 424021-01 | DEPRESSED CORNER FOR SIDEWALKS |
| 424026-01 | ENTRANCE/ALLEY PEDESTRIAN CROSSINGS |
| 424031-01 | MEDIAN PEDESTRIAN CROSSINGS |
| 606001-05 | CONCRETE CURB TYPE B AND COMB CONCRETE CURB AND GUTTER |

APPROVED ADA DETECTABLE WARNING TILES:

1. ADA SOLUTIONS - CAST IN PLACE REPLACEABLE
2. ARMOR TILE - CAST IN PLACE
3. DETECTILE - SLIMTEK II
4. TUFTILE - POLYMER WET-SET



**CITY OF BATAVIA
PUBLIC WORKS**

**SHEET: 1 OF 1
DATE: 8/18/20**

CURB RAMPS

STANDARD NO. 7.10